# **Safety Data Sheet**

Regulation EC No 1907/2006 Art.31

**Productname:** 

Ref.Nr.:

**AMBERCLENS** 

UDS000360 3 20150515 (EN)

Creationdate : Replaces:

15.05.15 Version: 1.0

UK10001

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

#### **AMBERCLENS**

Aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Cleaners - Heavy duty

#### 1.3. Details of the supplier of the safety data sheet

CRC Industries UK Ltd.
Ambersil House - Wylds Road
Castlefield Industrial Estate
TA6 4DD Bridgwater Somerset
United Kingdom

Tel.: +44 1278 727200 Fax.: +44 1278 425644 E-mail : hse.uk@crcind.com

#### 1.4. Emergency telephone number

(+44)(0)1278 72 7200

MALTA: MEDICINES AND POISONS INFO OFFICE: 2545 6504

# SECTION 2: Hazards identification

# 2.1. Classification of the substance or mixture

### Classification according to Regulation (EC) No 1272/2008

**Physical:** Aerosols, category 1

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Eye irritation, category 2 Causes serious eye irritation.

Not classified

Not classified

# Environment:

Health:

# Classification according to 67/548/EEC or 1999/45/EC:

**EXTREMELY FLAMMABLE** 

Health: Not classified

**Physical:** R12: Extremely flammable.

# **Safety Data Sheet**

# Regulation EC No 1907/2006 Art.31

Productname: AMBERCLENS Creationdate: 15.05.15 Version: 1.0

**Ref.Nr.:** UDS000360\_3\_20150515 (EN) **Replaces**: UK10001

**EXTREMELY FLAMMABLE** 

**Environment:** Not classified

### 2.2. Label elements

### Labelling according to Regulation (EC) No 1272/2008

# Hazard pictogram(s):





Signal word: Danger

**Hazard statement(s):** H222 : Extremely flammable aerosol.

H229 : Pressurised container: May burst if heated.

H319: Causes serious eye irritation.

**Precautionary statement(s):** P102 : Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P280 : Wear protective gloves/protective clothing/eye protection/face

protection.

P410/412: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F.

P501-2: Dispose of contents/container to an authorised waste collection point.

Regulation (EC) No

648/2004 on detergents: aliphatic hydrocarbons5 - 15 %

anionic surfactants < 5 %

perfumes benzyl alcohol, limonene

### 2.3. Other hazards

None

# **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

Not applicable.

### 3.2. Mixtures

Hazardous ingredient	CAS-nr.	EC-nr	w/w %	symbol	R- phrases*	Notes
Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	68512-91- 4	270-990-9	5-10	F+	12	K,G
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	203-539-1	1-5		10-67	Α
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	200-661-7	1-5	F,Xi	11-36-67	В
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	64742-47- 8	(926-141- 6)	1-5	Xn	65-66	В

**Ref.Nr.:** UDS000360\_3\_20150515 (EN) **Replaces:** UK10001

Glycine, N-methyl-N-(1-oxododecyl)-, sodium salt	137-16-6	205-281-5	<3	Т	23-38-41	
Explanation notes						
A : substance with Community workplace exposure limit						
B : substance with national established workplace exposure limit						
G: exempted from the obligation to register in accordance with art.2(7)(a)of REACH Regulation No 1907/2006						
K: not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)						

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %		Hazard statement	Notes
Hydrocarbons, C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	-	68512- 91-4	270- 990-9	5-10	Press. Gas, Flam. Gas 1	H280,H220	K,G
1-methoxy-2-propanol; monopropylene glycol methyl ether	01-2119457435- 35	107-98-2	203- 539-1	1-5	Flam. Liq. 3, STOT SE 3	H226,H336	А
propan-2-ol; isopropyl alcohol ;isopropanol	01-2119457558- 25	67-63-0	200- 661-7	1-5	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3	H225,H319,H336	В
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	01-2119456620- 43	64742- 47-8	(926- 141-6)	1-5	Asp. Tox. 1	H304	В
Glycine, N-methyl-N-(1-oxododecyl)-, sodium salt		137-16-6	205- 281-5	<3	Skin Irrit. 2, Eye Irrit. 2, Acute Tox. 3	H315,H319,H331	

#### **Explanation notes**

A : substance with Community workplace exposure limit

B : substance with national established workplace exposure limit

G: exempted from the obligation to register in accordance with art.2(7)(a) of REACH Regulation No 1907/2006

K: not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)

(\* Explanation phrases : see chapter 16)

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

Contact with eyes :	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  If eye irritation persists: Get medical advice/attention.
Contact with skin :	Take off contaminated clothing and wash before reuse.  IF ON SKIN: Wash with plenty of soap and water.  If skin irritation occurs: Get medical advice/attention.
Inhalation :	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Ingestion :	If swallowed accidentally, do not induce vomiting and seek medical advice.

# 4.2. Most important symptoms and effects, both acute and delayed

Inhalation :	Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion:	May cause gastrointestinal disturbances
	Symptoms: sore throat, abdominal pain, nausea, vomiting
Skin contact :	May cause irritation.
	Symptoms : redness and pain
Eye contact :	Irritating to eyes
	Symptoms : redness and pain

**Ref.Nr.:** UDS000360\_3\_20150515 (EN) **Replaces**: UK10001

#### 4.3. Indication of any immediate medical attention and special treatment needed

**General Advice :** If you feel unwell, seek medical advice (show the label where possible If symptoms persist always call a doctor

### SECTION 5: Firefighting measures

### 5.1. Extinguishing media

foam, carbon dioxide or dry agent

## 5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C Forms hazardous decomposition products CO,CO2

#### 5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes

# SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources Ensure adequate ventilation Wear suitable protective clothing and gloves.

### 6.2. Environmental precautions

Do not allow to enter public sewers and watercourses
If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

### 6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material Place in appropriate container

### 6.4. Reference to other sections

For further information see section 8

# SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Ref.Nr.:** UDS000360\_3\_20150515 (EN) **Replaces:** UK10001

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Equipment should be earthed

Use explosion-proof electrical/ventilating/lighting/.../equipment.

Use only non-sparking tools.

Do not breathe aerosols or vapours.

Ensure adequate ventilation

Avoid contact with skin and eyes.

Wash thoroughly after use

Wear protective gloves/protective clothing/eye protection/face protection.

Eyewash bottles should be available

## 7.2. Conditions for safe storage, including any incompatibilities

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C. Keep out of reach of children.

### 7.3. Specific end use(s)

Cleaners - Heavy duty

# SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

### **Exposure limits:**

Hazardous ingredient	CAS-nr.	method	
EU established exposure limits:			
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	TWA	100 ppm
		STEL	150 ppm
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	TWA	400 ppm
		STEL	500 ppm
National established exposure limits, United Kingdom			
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	TWA	100 ppm
		STEL	150 ppm
propan-2-ol; isopropyl alcohol; isopropanol	67-63-0	TWA	400 ppm
		STEL	500 ppm

## 8.2. Exposure controls

Control procedures :	Ensure adequate ventilation
	Keep away from heat and sources of ignition
	Take precautionary measures against static discharges
Personal protection :	Take precautions to avoid contact with skin and eyes when handling the product.
·	Ensure adequate ventilation
inhalation :	In case of insufficient ventilation, wear suitable respiratory equipment.
hands and skin :	Wear suitable protective gloves against chemicals

**Ref.Nr.:** UDS000360\_3\_20150515 (EN) **Replaces:** UK10001

Recommended gloves: Nitrile

eyes: Wear safety goggles.

**Environmental protection:** Avoid release to the environment.

Collect spillage.

# SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

Apperance : physical state :Liquid under pressure.colour :Colourless to yellow.odour :Characteristic odor.

 pH:
 10

 Boiling point/range:
 82 °C

 Flash point:
 12 °C

**Evaporation rate :** Not available.

Explosion limits : upper limit : 15 % lower limit : 0.6 %

Vapour pressure : Not available.

Relative density: 0.962 g/cm3 (@ 20°C).

Solubility in water : Soluble in water

Auto-ignition :225 °CViscosity :Not available.

# 9.2. Other information

**VOC:** 221 g/l

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

No hazardous reactions known if used for its intended purpose

# 10.2. Chemical stability

Stable

### 10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

### 10.4. Conditions to avoid

Avoid overheating

### 10.5. Incompatible materials

**Ref.Nr.:** UDS000360\_3\_20150515 (EN) **Replaces**: UK10001

Strong oxidising agent

## 10.6. Hazardous decomposition products

CO,CO2

# SECTION 11: Toxicological information

# 11.1. Information on toxicological effects

# Information on likely routes of exposure:

Inhalation: Inhalation of solvent vapours may give rise to nausea, headaches and

dizziness

Ingestion: May cause gastrointestinal disturbances

**Skin contact :** May cause irritation. **Eye contact :** Irritating to eyes

## Toxicological data:

Hazardous ingredient	CAS-nr.	method	
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	LD50 oral rat	4016 mg/kg
		LC50 inhal.rat	27596 mg/l
		LD50 derm.rabit	2000 mg/kg
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 20 mg/l
		LD50 derm.rabit	> 5000 mg/kg
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	64742-47-8	LD50 oral rat	> 5000 mg/kg
		LD50 derm.rabit	> 5000 mg/kg

# **SECTION 12: Ecological information**

## 12.1. Toxicity

Not classified

## **Ecotoxicological data:**

Hazardous ingredient	CAS-nr.	method	
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	LC50 fish	6812 mg/l
		EC50 daphnia	23300 mg/l
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	IC50 algae	> 1000 mg/l
		LC50 fish	> 1000 mg/l
		EC50 daphnia	> 1000 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	64742-47-8	IC50 algae	1000 mg/l
		LC50 fish	1000 mg/l

**Productname:** AMBERCLENS

**Ref.Nr.:** UDS000360\_3\_20150515 (EN)

Creationdate: 15.05.15 Version: 1.0

Replaces: UK10001

EC50 daphnia 1000 mg/l

### 12.2. Persistence and degradability

No information available

### 12.3. Bioaccumulative potential

No information available

### 12.4. Mobility in soil

Soluble in water

#### 12.5. Results of PBT and vPvB assessment

No information available

#### 12.6. Other adverse effects

No information available

# SECTION 13: Disposal considerations

# 13.1. Waste treatment methods

**Product:** This material and its container must be disposed of in a safe way.

Do not discharge into drains or the environment, dispose to an authorised

waste collection point.

**National regulations:** Disposal should be in accordance with local, state or national legislation

### SECTION 14: Transport information

### 14.1. UN number

UN-number: 1950

## 14.2. UN proper shipping name

Proper shipping name: AEROSOLS

### 14.3. Transport hazard class(es)

Class: 2.1 ADR/RID - Classification code: 5F

### 14.4. Packing group

**Ref.Nr.:** UDS000360\_3\_20150515 (EN) **Replaces:** UK10001

Packing group: Not applicable.

#### 14.5. Environmental hazards

ADR/RID - Environmentally hazardous:

IMDG - Marine pollutant:
IATA/ICAO - Environmentally hazardous:

No

### 14.6. Special precautions for user

ADR/RID - Tunnelcode:	(D)
IMDG - Ems:	F-D, S-U
IATA/ICAO - PAX:	203
IATA/ICAO - CAO	203

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

# SECTION 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements. Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

EU-directive 99/45/EC

Regulation (EC) No 1272/2008 (CLP) Regulation (EC) No 1907/2006 (REACH)

### 15.2. Chemical safety assessment

No information available

### SECTION 16: Other information

\*Explanation risk-phrases: R10: Flammable.

R11: Highly flammable. R12: Extremely flammable. R23: Toxic by inhalation. R36: Irritating to eyes. R38: Irritating to skin.

R41: Risk of serious damage to eyes.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

\*Explanation hazard statements: H220: Extremely flammable gas.

H225: Highly flammable liquid and vapour.

**Ref.Nr.:** UDS000360\_3\_20150515 (EN) **Replaces**: UK10001

H280 : Contains gas under pressure; may explode if heated.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H336: May cause drowsiness or dizziness.

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.