



Pakex (UK) Plc, No 1, Prime Point, Bessemer Road, Welwyn Garden City, Herts, AL7 1FE
Tel: 01707 384858 | Fax: 01707 332838 | Email: sales@pakexuk.com | web : www.pakexuk.com

DATA SHEET- SINGLE SIDED FOAM

PROPERTIES	ISO STANDARD / UNIT
TENSILE STRENGTH	ISO 1798 / KPA >250
WATER ABSORPTION (7 DAYS)	DIN-53428 / % <1
TECHNICAL DETAILS	UNIT / VALUE
ADHESIVE	HOLT MELT RUBBER / 35GSM
AMBER GLASSINE LINER	GSM / 80
CARRIER	PE FOAM / 1MM - 12MM
PEEL ADHESION TO STEEL 180°	12000 N/M
LOOP TACK	1000 N/M
TEMPERATURE RANGE	C / '5°C TO 60°C
RECOMMENDED APPLICATION	C / '5°C TO 25°C
RELEASE FROM LINER	N/M / 10

THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE AND THE USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

DATE OF ISSUE : JULY 2017